

## Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/28/2010

Reviewed on 11/28/2010

### 1 Identification of the substance/mixture and of the company/undertaking

· **Product identifier**

· **Trade name:** BRUNOX® Epoxy

· **Relevant identified uses of the substance or mixture and uses advised against**

· **Application of the substance / the preparation**

Coating material  
rust neutraliser and epoxy primer

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

BRUNOX Korrosionsschutz GmbH  
Postfach 100127  
85001 Ingolstadt

Tel. + 49/ (0) 841 961 29 04  
Fax + 49/ (0) 841 961 29 13  
E-mail: office@brunox.com

BRUNOX AG  
Tunnelstrasse 6  
CH - 8732 Neuhaus/SG

Tel. +41/ (0)55 285 80 80  
Fax +41/ (0)55 285 80 81  
E-mail: office@brunox.com

· **Information department:** Abteilung Produktsicherheit: Tel. +41/ (0)79 372 34 44

· **Emergency telephone number:**

Toxikologisches Informationszentrum  
CH - 8030 Zürich, Freiestrasse 16  
Tel. +41/ 044 251 51 51

Notruf - CH - : 145                      Notruf - D - : Giftnotrufzentrale 030 19240  
Notruf - AT - : 01 4064343              EUROPÄISCHE NOTRUFNR. : 112

### 2 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

108-10-1	4-methylpentan-2-one	⚠ H225; ⚠ H332; H319; H335	10-25%
107-98-2	1-methoxy-2-propanol	⚠ H226	2.5-10%
67-63-0	propan-2-ol	⚠ H225; ⚠ H319; H336	2.5-10%
64-18-6	formic acid	⚠ H314	2.5-10%
112-34-5	2-(2-butoxyethoxy)ethanol	⚠ H319	2.5-10%

### 3 Hazards identification

· **Classification of the substance or mixture**



GHS02 Flame

H225 Highly flammable liquid and vapour.

(Contd. on page 2)

USA

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 11/28/2010

Reviewed on 11/28/2010

(Contd. of page 1)



GHS07

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H333 May be harmful if inhaled.

• **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Irritant

Irritating to eyes and skin.



Highly flammable

Highly flammable.

• **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

• **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

• **Label elements**

• **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with directives on hazardous materials.

• **Code letter and hazard designation of product:**



Irritant  
Highly flammable

• **Risk phrases:**

Highly flammable.  
Irritating to eyes and skin.

• **Safety phrases:**

Keep out of the reach of children.  
Keep container tightly closed and in a well-ventilated place.  
Do not breathe fumes/aerosol.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
If swallowed, seek medical advice immediately and show this container or label.  
Use only in well-ventilated areas.

• **Classification system:**

• **NFPA ratings (scale 0 - 4)**



Health = 1  
Fire = 3  
Reactivity = 0

• **HMIS-ratings (scale 0 - 4)**

HEALTH	1
FIRE	3
REACTIVITY	0

Health = 1  
Fire = 3  
Reactivity = 0

(Contd. on page 3)

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 11/28/2010

Reviewed on 11/28/2010

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**4 First aid measures**

- **Description of first aid measures**
- **After inhalation:**  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** A person vomiting while lying on their back should be turned onto their side.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Firefighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 4)  
USA

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 11/28/2010

Reviewed on 11/28/2010

(Contd. of page 3)

See Section 13 for disposal information.

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**  
Keep receptacles tightly sealed.  
Store in cool, dry place in tightly closed receptacles.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store only in the original receptacle.  
Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
**108-10-1 4-methylpentan-2-one**  
PEL 410 mg/m<sup>3</sup>, 100 ppm  
REL Short-term value: 300 mg/m<sup>3</sup>, 75 ppm  
Long-term value: 205 mg/m<sup>3</sup>, 50 ppm  
TLV Short-term value: 307 mg/m<sup>3</sup>, 75 ppm  
Long-term value: (205) 82 mg/m<sup>3</sup>, (50) NIC-20 ppm  
(BEI);NIC-A3  
**107-98-2 1-methoxy-2-propanol**  
REL Short-term value: 540 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 360 mg/m<sup>3</sup>, 100 ppm  
TLV Short-term value: 553 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 369 mg/m<sup>3</sup>, 100 ppm  
**67-63-0 propan-2-ol**  
PEL 980 mg/m<sup>3</sup>, 400 ppm  
REL Short-term value: 1225 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
TLV Short-term value: 984 mg/m<sup>3</sup>, 400 ppm  
Long-term value: 492 mg/m<sup>3</sup>, 200 ppm  
BEI

(Contd. on page 5)

USA

## Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/28/2010

Reviewed on 11/28/2010

(Contd. of page 4)

**64-18-6 formic acid**PEL 9 mg/m<sup>3</sup>, 5 ppmREL 9 mg/m<sup>3</sup>, 5 ppmTLV Short-term value: 19 mg/m<sup>3</sup>, 10 ppmLong-term value: 9.4 mg/m<sup>3</sup>, 5 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Fluid

- **Color:**

Amber colored

- **Odor:**

Characteristic

- **Odour threshold:**

Not determined.

(Contd. on page 6)

USA

## Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/28/2010

Reviewed on 11/28/2010

(Contd. of page 5)

· <b>pH-value at 20°C (68°F):</b>	4
· <b>Change in condition</b>	
<u>Melting point/Melting range:</u>	Undetermined.
<u>Boiling point/Boiling range:</u>	82°C (180°F)
· <b>Flash point:</b>	13°C (55°F)
· <b>Ignition temperature:</b>	270°C (518°F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<u>Lower:</u>	1.7 Vol %
<u>Upper:</u>	9.0 Vol %
· <b>Vapor pressure at 20°C (68°F):</b>	8 hPa (6 mm Hg)
· <b>Density at 20°C (68°F):</b>	1 g/cm <sup>3</sup> (8.345 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with</b>	
<u>Water:</u>	Not miscible or difficult to mix.
· <b>Segregation coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<u>Dynamic:</u>	Not determined.
<u>Kinematic:</u>	Not determined.
· <b>Solvent content:</b>	
<u>Organic solvents:</u>	39.6 %
<u>VOC content:</u>	39.6 %
	396.5 g/l / 3.31 lb/gl
<u>Solids content:</u>	47.3 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 7)

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 11/28/2010

Reviewed on 11/28/2010

(Contd. of page 6)

**11 Toxicological information****· Information on toxicological effects****· Acute toxicity:****· LD/LC50 values that are relevant for classification:****108-10-1 4-methylpentan-2-one**

Oral LD50 2080 mg/kg (rat)

Dermal LD50 16000 mg/kg (rab)

Inhalative LC50/4 h 8.3-16.6 mg/l (rat)

**· Primary irritant effect:****· on the skin:**

Bei längeren und/oder häufigem Hautkontakt sind Reizerscheinungen möglich.

Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis.

Irritant to skin and mucous membranes.

**· on the eye:** Irritating effect.**· Sensitization:** No sensitizing effects known.**· Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

**12 Ecological information****· Toxicity****· Aquatic toxicity:** No further relevant information available.**· Persistence and degradability** No further relevant information available.**· Behavior in environmental systems:****· Bioaccumulative potential** No further relevant information available.**· Mobility in soil** No further relevant information available.**· Additional ecological information:****· General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**· Other adverse effects** No further relevant information available.**13 Disposal considerations****· Waste treatment methods****· Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**· Uncleaned packagings:****· Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 8)

## Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/28/2010

Reviewed on 11/28/2010

(Contd. of page 7)

### 14 Transport information

· DOT regulations:



- Hazard class: 3
- Identification number: UN1866
- Packing group: II
- Proper shipping name (technical name): RESIN SOLUTION
- Label: 3

· Land transport ADR/RID (cross-border):



- ADR/RID class: 3 Flammable liquids
- Danger code (Kemler): 33
- UN-Number: 1866
- Packaging group: II
- Label: 3
- UN proper shipping name: 1866 RESIN SOLUTION, special provision 640D

· Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1866
- Label: 3
- Packaging group: II
- EMS Number: F-E,S-E
- Marine pollutant: No
- Proper shipping name: RESIN SOLUTION

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1866
- Label: 3
- Packaging group: II
- Proper shipping name: RESIN SOLUTION

- UN "Model Regulation": UN1866, RESIN SOLUTION, 3, II
- Special precautions for user Warning: Flammable liquids
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.



## Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/28/2010

Reviewed on 11/28/2010

(Contd. of page 8)

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**  
None of the ingredients is listed.
- **Section 313 (Specific toxic chemical listings):**  
108-10-1 4-methylpentan-2-one  
67-63-0 propan-2-ol  
64-18-6 formic acid
- **TSCA (Toxic Substances Control Act):**  
All ingredients are listed.
- **Proposition 65**
- **Chemicals known to cause cancer:**  
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for females:**  
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for males:**  
None of the ingredients is listed.
- **Chemicals known to cause developmental toxicity:**  
None of the ingredients is listed.
- **Carcinogenic categories**
- **EPA (Environmental Protection Agency)**  
108-10-1 4-methylpentan-2-one 1
- **IARC (International Agency for Research on Cancer)**  
67-63-0 propan-2-ol 3  
1401-55-4 Tannins 3
- **NTP (National Toxicology Program)**  
None of the ingredients is listed.
- **TLV (Threshold Limit Value established by ACGIH)**  
67-63-0 propan-2-ol A4
- **NIOSH-Ca (National Institute for Occupational Safety and Health)**  
None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**  
None of the ingredients is listed.
- **Product related hazard informations:**  
The product has been classified and marked in accordance with directives on hazardous materials.
- **Hazard symbols:**



Irritant  
Highly flammable

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 11/28/2010

Reviewed on 11/28/2010

(Contd. of page 9)

- **Risk phrases:**  
Highly flammable.  
Irritating to eyes and skin.
- **Safety phrases:**  
Keep out of the reach of children.  
Keep container tightly closed and in a well-ventilated place.  
Do not breathe fumes/aerosol.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
If swallowed, seek medical advice immediately and show this container or label.  
Use only in well-ventilated areas.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing MSDS:** Abteilung Produktsicherheit

- **Contact:** siehe Seite 1 / see page 1

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

USA